

Outdoor Construction 1000w LED Balloon Light Tower with 360° Illumination Cold White

Basic Information

• Place of Origin: Guangdong, China

• Brand Name: UShineray

Model Number: YXR-BL-1000W-A

• Minimum Order Quantity: 2 pieces

• Price: \$798.00/pieces 2-99 pieces



Product Specification

Color Temperature(CCT): 5000K
IP Rating: IP65
Beam Angle(°): 360°
CRI (Ra>): 70

Input Voltage(V): AC90-305V

• Lamp Luminous 160

Efficiency(lm/w):

Lamp Luminous Flux(Im): 165000
Warranty(Year): 5-Year
Working Lifetime(Hour): 50000
Working Temperature(°C): -20~60
Color Rendering Index(Ra): 70

• Emitting Color: Cold White, Warm White, White

• Power Supply: Solar, AC, DC

• Light Source: LED



More Images









Products Description



Why Choose Us?

- 1. Original design function: Filtration device Dust absorption
- 2. Wide area coverage with 360° illumination
- 3. Glare-free, diffused lighting; Lightweight and portable 4. High Efficiency ≥160lm/W; Low power consumption;
- 5. Water-resistant LED balloon light rated to IP65 standard 6. Dimmable (≤320W); On-off button switch 7. Foldable tripod and cover, easy quick setup; 8. Weather resistant design including a waterproof, UV resistant and fire retardant balloon; Life span > 50,000hrs;
- 9. Balloon material: Waterproof, translucent, anti-UV, flame-retardant outdoor gauze.

Product Paramenters

i ioduct i ai	amemers	•					
Model No. YXR-BL	500W-A	600W-A	700W-A	800W-A	1000W- A	1200W-A	1400W- A
Power	500W	600W	700W	800W	1000W	1200W	1400W
Lumen (Im)	80000	96000	112000	128000	165000	192000	231000
Lamp Weight (kg)	11.5	18.1	18.5	18.8	20	21	22
Inflated Dimension	D70*H60		D90*H60			D110*H85	
Light Efficiency	160lm/W						
LED Chips	Lumileds 2835						
Voltage	AC 90-305V						

 CRI
 ≥70Ra

 CCT
 5000K

 IP Grade
 IP65

Work Temp -20~60°C

Tripod

Height(min-max) Collapsed Height Net Weight

1620-3800mm 1.8m 11.5kg

Details Images



- Color temperature adjustable, Dimmable(≤320W).
- Foldable tripod and cover; Lightweight; Portable; Easy quick setup.
- Glare-free; Diffused light; 360° illumination; Dimmable; On-off button switch.
- ♦ High Efficiency ≥160lm/W; Low power consumption.
- Weather resistance; Life span > 50,000hrs; Low maintenance.
- Bailoon material: Waterproof, translucent, anti-UV, flame -retardant.
- Filtration device: Dust absorption.







LED BALLOON LIGHT







LED Balloon Light

Specifications

	Please	MOVES 1000M / SUDMI		
	Yillage	A090-277V		
	Frequency	50/10-W		
	**	1636		
	LES Smar	(combate 2016		
Lamp	LED Chies	Utherway		
	Carter	9600m / 16000m / 16000m		
	CRE	TORa		
	601	2000 4000 (Alpanes)		
	Inflated Clarectures	400x000mm		
	Lang Hogie	4 hg 10ng 10ng		
	Height (min)	10°0-1900mm		
Stand	Column regit	1.86m		
	Not streight	6.bg		





Package Included















(1)					
GOW Flathword Area(or) (Area(or)) (Area(or))	1	-	4 301 4	12.6 190 6.6	
100W Reduction Area(or') or resolution to the control of the control or the contr	3 154	90 33	201	14 815 85	
120W Reduction or rively areas (14") or rively areas (14") or 150 (40")	2 20	* 10 27	200	14.9 600 6.5	

Product Size



60W/100W/120W

















Specifications







Package Included





















150W/200W/320W







I LED BALLOON LIGHT











Specifications

	-	1956.004
	Power	900W
	Voltage	A096-000V
	Frearry	1010-9
	17 635	16.00
Lamp	180 Driver	Institute
-	LED CHEA	Landon 2020
	Samen	80800m
	ON	790a
	1001	5000K
	Inflated Dimension	700ner900nee
	Lane Wagit	Tring
Tripod	regionnes	1630-3600nm
mpos.	Colopset Height	1.5n
	NetWinget	15.5kg

Product Features



Package Included





+ Optional









Product Size



500W





















Specifications

	Power	400W / T00W / 508W		
	Yethqu	ACIO SERV		
	Property	2040-9		
		10.99		
	LEDONA	Partition		
Lamp	LED Chips	Lummak 2000		
	Lamen	36000m1110000m1108000m		
	64	70/a		
	007	9004		
	MacDreson .	907400mm		
	Samp Progra	Militag 18 Sept 16 Sep		
	(Magneton code)	1605 1809 wn		
Tripod	Collegent Hospit	184		
	that thought	11.949		

Product Features













Optional











◆ Product Size



600W/700W/800W







LED BALLOON LIGHT

Product Features





BL-1000W-1400W-A

LED Balloon Light Specifications



•					
1000W	Ma(kuem) Area(m²) Fall gover(in) Half gover(in)	1083	* m 118 m2	* E 3 0	49 8008 6.5 6.5
1200W	Reducini) Area(mi) Full power(h) Half power(h)	1 m m 17	4 00 343 71	4 20 40 31	100 110 11
1400W	Reducini) Area(m1) Fut gover(h) Helf power(h)	1 401 211	4 00 00 00 00 00 00 00 00 00 00 00 00 00	20 40 20 20 20	36 8800 03 03


























Company Profile

OUR FACTORY









FAQ

Q1. Are you a manufacturer?

Yes, we have our own factory with over 10 years R&D and manufacture experience base on ISO quality management since 2011.

Q2. Do you have any MOQ limit for led light order?

No MOQ, 1pcs for sample checking is available.

Q3. Can I get a lower price for large quantity order?

Yes, please check with our sales staff for the details.

Q4. How about the lead time of UFO LED High Bay Light?

Our standard lead time for sample is 3-5 days, and normal order lead time is 7-10 days. For the large order lead time, please also check with our sales team.

Q5. Can you provide OEM and ODM service?

we can provide OEM and ODM product, with customized label design on the product and carton box. Or customized carton box, and laser print logo on the lamp fixture.

Q6. What is the payment terms of your formal order?

+8613410523891

We accept payment via T/T, Paypal, Western Union, and we offer EXW terms.

Q7. How to deal with the defective?

All of our product are produced in strict quality control system, the defective rate is less than 0.2% according to our shipment records. We offer 3-5 years warranty for this product, if there is any defective during the warranty, please provide the picture or video for the working situation of the defective lights, we will ship the new lights to you within a few days or send it together with your next order.



joy@ushineray.com 4F, Building C, Junxing Optoelectronic Industrial Park, Fuyuan 2nd Road, FuHai Street, Bao'an District, Shenzhen

ushineraylight.com