

250W Modern Outdoor LED Floodlight IP65 Waterproof

Basic Information

• Place of Origin: Guangdong, China

• Brand Name: UShineray

• Certification: EMC, RoHS, CQC, CCC, CE, FCC

Model Number: YXR-FL-250W-S

• Minimum Order Quantity: 1pcs

Packaging Details:
 1 pcs in Inner box

1 pcs per carton

Carton gross weight: 13kg

Payment Terms: T/T, Paypal, Western Union
 Supply Ability: 2000 Piece/Pieces per Week



Product Specification

Application: GardenColor Temperature(CCT): 2700-6500k

• IP Rating: IP66

Lamp Body Material: Aluminum Alloy
Beam Angle(°): 30/60/90/120

• CRI (Ra>): 70

Input Voltage(V): AC100-270VLamp Luminous 160/170/190

Efficiency(lm/w):

Lamp Luminous Flux(lm): 4800
Warranty(Year): 3-Year
Working Lifetime(Hour): 50000
Working Temperature(°C): -40 - 60
Color Rendering Index(Ra): 70
Light Source: LED



More Images



Product Description



Specification

Model S YXR-FL-	30W-S	60W-S	100W- S	200W-S	300W-S	400W-S	500W-S	
Power	30W	60W	100W	200W	300W	400W	500W	
Lumen	4800	9600	16000	32000	48000	64000	80000	
Size	L168*W 120*H36 .3 mm	L230*W 180*H69 .5 mm	L280* W215* H69.8 mm	L459.4* W322.5* H71.3 mm	L459.4* W322.5* H71.3 mm	L585*W420* H71.8 mm	L585*W420* H71.8 mm	
Weight(KG)	0.95	2.6	3.45	6.6	6.9	10.8	11	
Efficacy	160/170/190lm/w							
Led chips	Lumileds 2835							
Input Voltage	AC85-265V							
Color Temperatur e	2700-6500K							
CRI	≥80Ra							
Power Factor	>0.97							
Beam Angle	25°/45/°90°/120°							
Material	Aluminum alloy+PC lens							
IP Grade	IP66							

Details Images





PRODUCT DETAILS





ANGLE ADJUSTABLE 300°

Use it without worry even on rainy days. IP66 waterproof dustproof Can be used without worry even if it rains when working outdoors.



LMPACT RESIST ANTFURTHER

Adopts high hardness ADC12 aluminum alloy aluminum shell with excellent heat dissipation lighting fixture has excellent impact resistance







EXCELLENT HEAT DISSIPATION

Heat-resistant aluminum material is used, heat-resistant aluminum is luxuriously used, and heat dissipation performane is further improved with large comb-shaped fins.

PRODUCT DETAILS








Induction angle: 180° Mounting height: 2~8m 30°/60°/90°/120°













Widely used in shopping malls, exhibition halls, parking lots, gyms,billboards, parks, sculptures, green lighting projects, buildings, facades, as well as indoor and outdoor lighting for public corridors, stairs and corridors.



APPLICATION SCENARIO

Suitable for various scenarios



COURTYARD LIGHTING

Wide area lighting with sufficient lighting

-



ARCHITECTURAL LIGHTING

Wide area lighting with sufficient illumination, high display index, low light attenuation, long service life

_



BILLBOARD LIGHTING

Wide area lighting with sufficient lighting

_



Applications



4F, Building C, Junxing Optoelectronic Industrial Park, Fuyuan 2nd Road, FuHai Street, Bao'an District, Shenzhen